

### **FEATURES**

- Vent hole for drain
- · Backelite cover on handle



### **APPLICATION**

- · Hydraulic machines
- · Isolation for gauges
- Compressors

#### STANDARD SPECIFICATIONS

Type Pattern 1 (2 Way) Material **AISI 316 SS** 

1/2" NPT (F) [1/2" NPT (F) x 2 Nos for 3 Way] Instrument connection 1/2" BSP (F) [1/2" BSP (F) x 2 Nos for 3 Way]

1/2" NPT (M) / 1/2" BSP (M) Process connection

AISI 304 SS with Backelite cover Handle

Gaskets / Seals **PTFE** 100 bar Maximum working pressure Maximum working temperature 180°C

#### **DIMENSIONAL DRAWING**

## Pattern 1 Pattern 2 Handle OUTLET OUTLET Vent Hole Total Length Round Body Round Body INLET INLET

OUTLET

# A101

## GAUGE COCK



#### ORDERING CODES

1. TYPE		4	4. PROCESS CONNECTION		14N
1	Pattern 1 (2 Way)	1	12B	1/4" BSP (M)	1411
2	Pattern 2 (3 Way)		13B	3/8" BSP (M)	
	, , , ,		14B	½" BSP (M)	
2. MATERIAL			12N	1/4" NPT (M)	
Z. WATERIAL		MF	13N	3/8" NPT (M)	
MC	AISI 304 SS		14N	1/2" NPT (M)	
MF	AISI 316 SS		02B	1/4" BSP (F)	
MG	AISI 316L SS		03B	3/8" BSP (F)	
			04B	½" BSP (F)	
A INICEPLIMENT CONNECTION			02N	1/4" NPT (F)	
3. INSTRUMENT CONNECTION		04N	03N	3/8" NPT (F)	
12B	1/4" BSP (M)	0414	04N	½" NPT (F)	
13B	3/8" BSP (M)				
14B	½" BSP (M)				
12N	1/4" NPT (M)		5. OTHER OPTIONS		— хм
13N	3/8" NPT (M)		TC	Material test certificate 3.1	AIII
14N	½" NPT (M)		TM	Material test certificate 2.2	
02B	1/4" BSP (F)		TO	Certification for Oxygen service	
03B	3/8" BSP (F)		XM	Marking by engraving	
04B	1/2" BSP (F)		XL	Marking by laser	
02N	1/4" NPT (F)			ag 27 iacc.	
03N	3/8" NPT (F)				
04N	½" NPT (F)				
	• •				

Ordering Example: A101-1-MF-04N-14N-XM